



These sound attenuating enclosures for our larger units are constructed of satin finished stainless steel or lightweight powder coated aluminum panels. There is no internal framework. Instead, the individual panels are held together by a system of locating pins and latches as well as a strong, corrosion resistant stainless steel base which receives, locates and aligns the other members of the enclosure. The panels can be easily removed in seconds giving complete, unobstructed access to service the generator set. The panel covering the service side of the engine is specially designed to give immediate access. Customer specified penetrations can be provided at the time of manufacture for exhaust, control wiring and electrical cables as well as fuel and oil lines. For units equipped with a front power take-off, the front panel may also be removed quickly and with a minimum of labor.

- Sound transmission can be further retarded by choosing our double mounting option.
- Metal sound attenuating enclosures for our smaller generator sets not listed in the table below can be custom ordered from the factory.

MODEL	LENGTH	WIDTH	HEIGHT
30kW	59.00 in. (1499 mm)	28.00 in. (711 mm)	32.00 in. (813 mm)
40kW	67.50 in. (1715 mm)	31.25 in. (794 mm)	38.50 in. (978 mm)
45, 55 & 60kW	70.50 in. (1791 mm)	35.50 in. (902 mm)	38.50 in. (978 mm)
65kW	73.50 in. (1867 mm)	35.50 in. (902 mm)	38.50 in. (978 mm)
80, 90 & 99kW	90.00 in. (2286 mm)	41.00 in. (1041 mm)	42.50 in. (1080 mm)
125 & 150kW	93.00 in. (2362 mm)	45.00 in. (1143 mm)	44.50 in. (1130 mm)